

Get class-leading luxury and com



B3150SU

The new B50 Series tractors take compact tractor capability to the next level with user-friendly operation and outstanding productivity. Equipped with high quality Kubota engines and transmissions, they deliver the extra durability and reliability you demand for a wide range of jobs. The new integrated cab delivers spaciousness and an expanded field of vision for luxury that's beyond their class. Whether you're mowing, landscaping or doing light utility work, the new B50 Series is the best choice for durability, versatility and comfort.

B50 Series

Easy attach/detach implements give yo

LA534A FRONT LOADER



The LA534A front loader offers a large lifting capacity, perfect for landscaping or light utility work. The curved boom matches the new hood design for a sleek and modern appearance and offers a better field of vision during front load operations.



INTEGRATED LOADER VALVE AND JOYSTICK

Loader operations are more convenient with the 4-position valve and control lever. This fully integrated ergonomically positioned valve lets you attach the front loader and other front implements quickly and easily.



THIRD FUNCTION VALVE (Optional)

The optional 3rd function valve broadens the scope of the front loader operation by enabling use of a grapple bucket and other hydraulically controlled attachments. The 3rd function valve can be activated with buttons located on the grip of the joystick.



HYDRAULIC SPILL-GUARD

The spill-guard tilts the bucket forward as the loader is raised reducing spillage to make filling and dumping easier.

MID-MOUNT MOWER

Ultra-sturdy and highly versatile mid-mount mowers with a choice 60-inch or 72-inch cutting widths, feature cutting height adjustments from 1.5 - 4 inch in 0.5 inch increments.

Front Loader Specifications

Model		LA534A
Maximum lift height (to bucket pivot pin)	mm	2150
Clearance with attachment dump	mm	1712
Maximum dump angle	deg.	38.1
Max. rollback angle	deg.	28.6
Rated operating load (500 mm forward)	kg	350
Breakout force (pivot pin)	kg	1053
Breakout force (19.7in. forward)	kg	767

Mid Mount Mower Specifications

Model		RCK60-30B	RC72-30B
Type		Side Discharge	
Number of blades		3	
Mounting method		Floating	
Cutting width	in. (mm)	60 (1524)	72 (1826)
Cutting height	in. (mm)	1.5 to 4.0 (38 to 102)	
Adjustment of cutting height		Gauge wheel	
Weight	kg	170	210

Specifications

Model			B3150HD	B3150SUHD	B3150HDCC
Engine					
Type			E-TVCS, liquid cooled, 4-cylinder diesel		
Make, Model			V1505-E3-D26BH-A		
PTO horsepower	HP (kW)		23.7 (17.7)		
Engine gross horsepower*	HP (kW)		31.0 (22.8)		
Rated RPM	rpm		2500		
Bore and stroke	mm		78 × 78.4		
Displacement	cc		1498		
Air cleaner			Double element		
Lubrication			Forced lubrication		
Cooling system			Pressurized radiator		
Radiator fan			Radial air flow		
Capacities					
Fuel tank	ℓ		27		
Cooling system	ℓ		4.6		
Engine oil	ℓ		4.0		
Transmission case	ℓ		15		
Drive train					
Clutch			N/A		
Transmission			HST (3 ranges)		
Differential lock			Standard		
Final drive			Standard		
Brake			Multi-plate wet disc		
PTO					
Type			Independent		
Rear	rpm		540		
Mid	rpm		2400	N/A	2400
Hydraulics					
Type			Open center		
Pump			Dual pump		
Total pump output	ℓ/min.		33.1		
Hydraulic outlet			Rear outlet		
3-point hitch			Category I		
Hydraulic control system			Position control valve	Quarter inching valve	Position control valve
Lift capacity at lift point	kg		970		
24" behind LP	kg		760		
Cruise control			STD	OPT	STD
Steering			Hydraulic power steering		
Standard tyre size					
Farm (front / rear)			7-12 / 12.4-16		
Turf (front / rear)			24 × 8.50 - 12 / 13.6 - 16		
Industry (front / rear)			23 × 8.50 - 14R4 / 12.4 - 16R4		
Travelling speeds					
Forward (turf tyre / farm tyre)	km/h		0 - 18.0		
Reverse	km/h		0 - 13.5		
Dimensions					
Overall length (w/o 3P)	mm		2570		2900
Overall width (min. tread)	mm			1365	
Overall height	mm		2245		2150
Tread (front / rear)	mm			935 / 1050	
Wheelbase	mm			1666	
Ground clearance	mm			370	
Turning radius with brake	m			2.1	
Weight	kg		840		1035
Other Features					
Telescopic lower link ends			STD	N/A	STD
Drawbar				STD	
Seat suspension			Damper seat suspension	Coil spring	Damper seat suspension
Armrest			STD	N/A	STD
Generator			Dynamo		Alternator
Integrated cab			N/A		STD
Standard features			Loader valve, Tilt-steering, 12V power socket, Radio ready speaker (only on HDCC)		
Implements					
Mid mower			RCK60-30B / RC72-30B	N/A	RCK60-30B / RC72-30B
Loader				LA534A	

*SAE J1995

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only.

Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.

©2014 Kubota Corporation



KUBOTA Tractor Australia Pty Ltd

25-29 Permas Way, TRUGANINA Vic, 3029
 Freecall: 1800 334 653
 Email: sales@kubota.com.au

Web Site: <http://www.kubota.com.au>

CB Norwood Distributors Ltd

PO Box 1265, 888 Tremain Avenue,
 Palmerston North 0800 KUBOTA
 Tel: 06 356 4920 Fax: 06 356 4939

Web Site: <http://www.kubota.co.nz>